



MBP 648 A

M O D U L A R S Y S T E M

MBP 648 A

extended preamp

As far as the technical features are concerned, the MBP 648 A is identical to the MBP 648. It has been developed for specific recording purposes. Due to the separation of capsule and impedance transformer, small microphone systems can be realized with all MBHO capsules. This preamp includes a 3 m cable and a fixed capsule attachment at the bottom end.



No. 92 - 6481

specifications

preamp	MBP 648 (A)
phantom power	48 V
feed current	ca. 1,7 mA
electrical impedance	200 Ω
connector	XLR
size	\varnothing 21 x 25 mm

- Tip:
- recordings for movies
 - theatre
 - news desks
 - percussion
 - brass instruments
 - acoustic guitar

MBP 680

preamp with low cut filter

Think of the MBP 680 as a MBP 648 with these additional of the ability to accept our active battery cable (see 99-8030 and 99-8035). In the MBP 680 we have designed a voltage converter that is effective between 12 and 48 V at a very low current consumption. Need put together a solid microphone for fieldwork? Here it is!

The MBP 680 also features a switchable voice filter / low cut.

specifications

preamp	MBP 680
phantom power	12 - 48 V
feed current	ca. 1,9 mA
electrical impedance	200 Ω
connector	XLR
size	\varnothing 21 x 122 mm

- Tip:
- outdoor &
 - mobile recordings

No. 92 - 6800



MBP 680

M O D U L A R S Y S T E M